



NOTES

- 1 DESIGN PRESSURE 4.5MPA
- 2 THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
- 3 DIAGONAL DIFFERENCE MAX 10mm
- 4 TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C (GB/T 1804 CLASS C)
- 5 SEAL 0.01~0.05MPA NITROGEN GAS IN THE PRODUCT
- 6 OTHER STANDARDS JB/T11967 EN378-2.
- 7 THE INLET AND OUTLET PIPES ARE COPPER PIPES

PRODUCT PARAMETERS

TUBE NUMBER	133
TUBE TYPE	25.4*2- 20
TUBE MATERIAL	LLA9153(3F03)+Zn- H112
(LONG USING LIFE ALLOY)	φ38
MANIFOLD TYPE	LOUVERED 25.4*0.08 FPI 23
FIN TYPE	AA4343/3003/4343
FIN MATERIAL	85/48
PASS	



UNMARKED TOLERANCE X ±1.5 X.X ±1 X.XX ±0.5 ∠ ±1°	DESCRIPTION: Microchannel heat exchanger	
	MODEL: RC-1900-S	REV. A
VIEW ⊕ □	CODE: 021U0086R	CREAT: AUDIT:
	APPROVED BY CUSTOMER SIGNATURE:	PROCESS: APPROVE: