



NOTES

- DESIGN PRESSURE 4.5MPA
- THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
- DIAGONAL DIFFERENCE MAX 7mm
- TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C(GB/T 1804 CLASS C)
- SEAL 0.01~0.05MPA NITROGEN GAS IN THE PRODUCT
- OTHER STANDARDS JB/T11967 EN378-2
- THE INLET AND OUTLET PIPES ARE COPPER PIPES

PRODUCT PARAMETERS

TUBE NUMBER	61
TUBE TYPE	25.4*2- 20
TUBE MATERIAL	LLA9153(3F03)+Zn- H112
(LONG USING LIFE ALLOY)	
MANIFOLD TYPE	φ38
FIN TYPE	LOUVERED 25.4*0.08 FPI 23
FIN MATERIAL	AA4343/3003/4343
PASS	43/18



UNMARKED TOLERANCE X ±1.5 X.X ±1 X.XX ±0.5 < ±1°	DESCRIPTION: Microchannel heat exchanger	
	MODEL: RC-1700-S	REV. A
VIEW ⊕ ⊞	CODE: 021U0085R	CREAT: AUDIT:
	APPROVED BY CUSTOMER SIGNATURE:	PROCESS: APPROVE: