



NOTES
 1 DESIGN PRESSURE 4.5MPa
 2 THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
 3 DIAGONAL DIFFERENCE MAX 3mm
 4 TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C (GB/T 1804 CLASS C)
 5 SEAL 0.01~0.05MPa NITROGEN GAS IN THE PRODUCT
 6 OTHER STANDARDS JB/T11967 EN378-2
 7 THE INLET AND OUTLET PIPES ARE COPPER PIPES

PRODUCT PARAMETERS
 TUBE NUMBER 34
 TUBE TYPE 16*1.3-16
 TUBE MATERIAL LLA9153(3F03)+Zn- H112
 (LONG USING LIFE ALLOY)
 MANIFOLD TYPE φ20
 FIN TYPE LOUVERED 16*0.08 FPI 23
 FIN MATERIAL AA4343/3003/4343
 PASS 10/9/8/7



UNMARKED TOLERANCE X ±1.5 X.X ±1 X.XX ±0.5 ∠ ±1°	DESCRIPTION: Microchannel heat exchanger	
	MODEL: RC-1100-S	REV. A
VIEW ⊕ ⊞	CODE: 021U0081R	CREAT: AUDIT:
	APPROVED BY CUSTOMER SIGNATURE:	PROCESS: APPROVE: