



NOTES
 1 DESIGN PRESSURE 4.5MPA
 2 THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
 3 DIAGONAL DIFFERENCE MAX 7mm
 4 TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C(GB/T 1804 CLASS C)
 5 SEAL 0.01~0.05MPA NITROGEN GAS IN THE PRODUCT
 6 OTHER STANDARDS JB/T11967 EN378-2
 7 THE INLET AND OUTLET PIPES ARE COPPER PIPES

PRODUCT PARAMETERS
 TUBE NUMBER 61
 TUBE TYPE 25.4*2- 20
 TUBE MATERIAL LLA9153(3F03)+Zn- H112
 MANIFOLD TYPE φ38
 FIN TYPE LOUVERED 25.4*0.08 FPI 23
 FIN MATERIAL AA4343/3003/4343
 PASS 43/18



UNMARKED TOLERANCE X ±1.5 X.X ±1 X.XX ±0.5 < ±1°	DESCRIPTION: Microchannel heat exchanger		REV. A
	MODEL: RC-1700-I		
VIEW ⊕ □	CODE: 021U0092R	CREAT: AUDIT:	
	APPROVED BY CUSTOMER SIGNATURE:	PROCESS: APPROVE:	